



REGENCY PRO-SERIES™ Hi500 Large Wood Insert



Hi500 shown with decorative cast grille (digital catalytic monitor not shown).

FEATURES

- EPA 2020 certified
- Front mounted air adjustment & catalytic bypass
- Digital catalytic temperature monitor
- High performance brick-lined firebox
- Clean glass airwash system
- Heavy gauge steel log retainers
- Traditional cast iron door with ceramic glass
- 110° opening door for easy loading
- Quick access leveling bolts
- Rollers for easy installation
- 10-year 100% coverage on original catalyst

OPTIONS

- Black or timberline brown enamel finish
- Flush mount 2 speed blower
- Faceplates in two sizes
- Decorative cast grille
- Backing plates in two sizes
- Offset flue adaptor for installation flexibility
- Stainless steel liner kits
- Flue connectors
- Wrap insulation kits

SPECIFICATIONS

Maximum BTU*	78,000
Typical sq. ft. heated**	up to 2,600
Efficiency (EPA LHV)	79%
Max log size	22"
Burn time	Up to 14 hours
Emissions	1.3 g/h
Firebox size	2.6 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE

regency-fire.com