

HAMPTON® Hi1150 Small Non-Catalytic Wood Insert



The Hampton Hi1150 small cast iron wood insert offers a the traditional look and feel of cast iron with modern efficiency. The Hi1150 delivers up to 55,000 BTU of high efficiency heat throughout your home providing comfort and warmth to the living areas you spend time in. Decrease your heating bills and increase the value of your home with this beautiful Hampton insert.

STANDARD FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- o Decorative cast iron grille
- Cast iron exterior provides additional radiant heating
- Wood-finished handle
- Heavy duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- o Side mounted air adjustment
- o High performance brick-lined firebox reflects heat
- o Non-obtrusive air wash curtain keeps glass clean
- $\circ\quad$ Heavy gauge steel log retainers to stop logs from rolling

OPTIONS

- Metallic black or timberline brown enamel finish
- 2 speed blower
- Power outlet conversion
- Regency stainless steel flex liner kits
 (5.5" DIA) in 25 ft. and 35 ft. lengths
- Wrap insulation kits
- o Flue connectors

SPECIFICATIONS	
Maximum BTU*	55,000
Typical sq. ft. heated**	1,000 - 2,200
Efficiency (EPA LHV)	75%
Max log size	18"
Burn time	Up to 8 hours
Emissions	1.7 g/h
Firebox size	1.3 cu. ft.
Flue size	6"

MIN. FIREPLACE OPENING	
Width (front) x Height	25" x 19-5/8"
Depth (standard flue adapter)	15-1/16"
Depth (offset flue adapter)	17-11/16"

NOTE: The ember protection shown in these images may not accurately reflect the ember protection dimensions required for your area.

^{*} Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

^{**} Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.