



REGENCY CASCADES™ i1500

Small Wood Insert



i1500 shown with regular faceplate and black cast iron door (digital catalytic monitor not shown).

FEATURES

- EPA 2020 certified
- Front mounted air adjustment & catalytic bypass
- Air & bypass operating tool
- Digital catalytic temperature monitor
- High performance brick-lined firebox
- Clean glass airwash system
- Heavy gauge steel log retainers
- 10-year 100% coverage on original catalyst

OPTIONS

- Cast iron door with ceramic glass in black or nickel accent
- Regular or oversize faceplate (black trim included)
- Variable speed blower
- Standard or 4-1/2" offset flue adaptor
- Regency stainless steel flex liner kits
- Wrap insulation kits

SPECIFICATIONS

Maximum BTU*	55,000
Typical sq. ft. heated**	600 - 1,200
Efficiency (EPA LHV)	84%
Max log size	18"
Burn time	Up to 10 hours
Emissions	1.0 g/h
Firebox size	1.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE